



DHV-tested Equipment | Flying Equipment Database | Manufacturers / Dealers | Flying Schools | Clubs

DHV Databases

TECHNICAL DATA | DHV TESTREPORT LTF | DHV TESTREPORT EN | DATASHEET | PRINT



DHV TESTREPORT EN926-2:2014

UP KANGRI L

Type designation UP Kangri L
Type test reference no DHV GS-01-2473-19
Holder of certification [UP International GmbH](#)
Manufacturer [UP International GmbH](#)
Classification B
Winch towing Yes
Number of seats min / max 1 / 1
Accelerator Yes
Trimmers No



BEHAVIOUR AT MIN WEIGHT IN FLIGHT (90KG)

BEHAVIOUR AT MAX WEIGHT IN FLIGHT (115KG)

Test pilots



Harald Buntz

Sebastian Mackrodt

No release

No release

Inflation/take-off

Rising behaviour Smooth, easy and constant rising

en : einfaches Aufziehen, etwas Korrektur des Piloten erforderlich
No

Special take off technique required No

Landing

Special landing technique required No

Speeds in straight flight

Trim speed more than 30 km/h Yes

Yes

Speed range using the controls larger than 10 km/h Yes

Yes

Minimum speed Less than 25 km/h

Less than 25 km/h

Control movement

Symmetric control pressure Increasing

Increasing

Symmetric control travel Greater than 60 cm

Greater than 65 cm

Pitch stability exiting accelerated flight

Dive forward angle on exit Dive forward less than 30°

Dive forward less than 30°

Collapse occurs No

No

Pitch stability operating controls during accelerated flight

Collapse occurs No

No

Roll stability and damping

Oscillations Reducing

Reducing

Stability in gentle spirals

Tendency to return to straight flight Spontaneous exit

Spontaneous exit

en : Verhalten beim Verlassen einer vollständigen Steilspirale

en : Erstes Ansprechen des Gleitschirms (die ersten 180°)

en : keine unmittelbare Reaktion

Tendency to return to straight flight en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)

en : selbstständiges Ausleiten (G-Kraft abnehmend, Drehgeschwindigkeit abnehmend)

Turn angle to recover normal flight Less than 720°, spontaneous recovery

Less than 720°, spontaneous recovery

<u>Symmetric front collapse</u>	A	A
Entry Rocking back less than 45°		Rocking back less than 45°
Recovery Spontaneous in less than 3 s		Spontaneous in less than 3 s
Dive forward angle on exit Dive forward 0° to 30°		Dive forward 0° to 30°
Change of course Entering a turn of less than 90°		Keeping course
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>en : Symmetrischer Frontklapper mindestens 50% Flügeltiefe</u>	B	B
Entry Rocking back less than 45°		Rocking back less than 45°
Recovery Spontaneous in 3 s to 5 s		Spontaneous in 3 s to 5 s
Dive forward angle on exit Dive forward 0° to 30°		Dive forward 0° to 30°
Change of course Entering a turn of less than 90°		Keeping course
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>en : Symmetrischer Frontklapper im beschleunigten Flug mindestens 50% Flügeltiefe</u>	B	B
Entry Rocking back less than 45°		Rocking back less than 45°
Recovery Spontaneous in 3 s to 5 s		Spontaneous in 3 s to 5 s
Dive forward angle on exit Dive forward 30° to 60°		Dive forward 0° to 30°
Change of course Entering a turn of less than 90°		Keeping course
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>Exiting deep stall (parachutal stall)</u>	A	A
Deep stall achieved Yes		Yes
Recovery Spontaneous in less than 3 s		Spontaneous in less than 3 s
Dive forward angle on exit Dive forward 0° to 30°		Dive forward 0° to 30°
Change of course Changing course less than 45°		Changing course less than 45°
Cascade occurs No		No
<u>High angle of attack recovery</u>	A	A
Recovery Spontaneous in less than 3 s		Spontaneous in less than 3 s
Cascade occurs No		No
<u>Recovery from a developed full stall</u>	A	A
Dive forward angle on exit Dive forward 0° to 30°		Dive forward 0° to 30°
Collapse No collapse		No collapse
Cascade occurs (other than collapses) No		No
Rocking back Less than 45°		Less than 45°
Line tension Most lines tight		Most lines tight
<u>en : Kleiner einseitiger Klapper</u>	A	A
Change of course until re-inflation Less than 90°		Less than 90°
Maximum dive forward or roll angle Dive or roll angle 0° to 15°		Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation		Spontaneous re-inflation
Total change of course Less than 360°		Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)		en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No		No
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>en : Großer einseitiger Klapper</u>	B	B
Change of course until re-inflation 90° to 180°		90° to 180°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°		Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation		Spontaneous re-inflation
Total change of course Less than 360°		Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)		en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No		No
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>en : Kleiner einseitiger Klapper im beschleunigten Flug</u>	A	B
Change of course until re-inflation Less than 90°		90° to 180°
Maximum dive forward or roll angle Dive or roll angle 15° to 45°		Dive or roll angle 15° to 45°
Re-inflation behaviour Spontaneous re-inflation		Spontaneous re-inflation
Total change of course Less than 360°		Less than 360°
Collapse on the opposite side occurs en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)		en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs No		No
Cascade occurs No		No
en : Faltleinen wurden benutzt no		no
<u>en : Großer einseitiger Klapper im beschleunigten Flug</u>	B	B
Change of course until re-inflation 90° to 180°		90° to 180°

Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)	en : Nein (oder nur eine kleine Anzahl von eingeklappten Zellen mit selbstständiger Wiederöffnung)
Twist occurs	No	No
Cascade occurs	No	No
en : Faltleinen wurden benutzt	no	no

Directional control with a maintained asymmetric collapse

A

A

Able to keep course	Yes	Yes
180° turn away from the collapsed side possible in 10 s	Yes	Yes
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel

Trim speed spin tendency

A

A

Spin occurs No No

Low speed spin tendency

A

A

Spin occurs No No

Recovery from a developed spin

A

A

Spin rotation angle after release Stops spinning in less than 90° Stops spinning in less than 90°

Cascade occurs No No

B-line stall

A

A

Change of course before release Changing course less than 45° Changing course less than 45°

Behaviour before release Remains stable with straight span Remains stable with straight span

Recovery Spontaneous in less than 3 s Spontaneous in less than 3 s

Dive forward angle on exit Dive forward 0° to 30° Dive forward 0° to 30°

Cascade occurs No No

Big ears

B

B

Entry procedure Dedicated controls Dedicated controls

Behaviour during big ears Stable flight Stable flight

Recovery Spontaneous in 3 s to 5 s Recovery through pilot action in less than a further 3 s

Dive forward angle on exit Dive forward 0° to 30° Dive forward 0° to 30°

Big ears in accelerated flight

A

B

Entry procedure Dedicated controls Dedicated controls

Behaviour during big ears Stable flight Stable flight

Recovery Spontaneous in 3 s to 5 s Recovery through pilot action in less than a further 3 s

Dive forward angle on exit Dive forward 0° to 30° Dive forward 0° to 30°

Behaviour immediately after releasing the accelerator while maintaining big ears Stable flight Stable flight

Alternative means of directional control

A

A

180° turn achievable in 20 s Yes Yes

Stall or spin occurs No No

Any other flight procedure and/or configuration described in the user's manual

No other flight procedure or configuration described in the user's manual